





Interface® | FastForward

SPECIFICATION


Product definition	Tufted Plain Level Cut Tile	Style number	6081400005
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	520g/m ² ± 10%	Radiant panel	(EN ISO 9239/1) Bfl S1 (EN ISO 13501)
Total Weight	4200g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition
Pile Height	1.7 ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	5.4 mm ± 0.3 mm	Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	5/64 - 50.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	206640 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105 B02)
Backing Type	Graphlex®	Tiles per Box	20 - 5 m ² (50 x 50 cm ± 0.2%)

CE
0336-CPD-8538
EN 14041:2004






EN 1307




Brick Ashlar Non-Directional




F531B645 19.6




33





Environmental Protection Scheme
Certificate Number EHP-407





Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications