

Interface® | Heuga 580

SPECIFICATION

Product definition	Tufted Plain Level Loop Tile	Style number	60580
Pile Material	100% BCF Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	580 g/m ² ± 5%	Radiant panel	Euroclass Bfl S1 : colours 5101 upto 5160 Euroclass Cfl S1 : colours 6801 upto 6874 (EN ISO 9239/1)(EN ISO 13501)
Effective pile yarn weight	375 g/m ² ± 10%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Total Weight	4229 g/m ² ± 5%	Castor Chair Rating	≥ 2,4 (EN 985)
Pile Height	3,1 mm ± 0,3 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Total Thickness	6,2 mm ± 0,3 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >< 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Gauge/Ends per 10cm	1/10 - 41	Colour Fastness - Light	>7 (ISO 105/B02)
Tufts per m²	164,000 ± 5%	Tiles per Box	20 - 5 m ² (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		

CE
06
0336-CPD-8538

Bfl-s1

DS

EN 1307

Monolithic Quarter Turn

Gut

11894

25 dB

NF CSTB

UPEC

Environmental Profile Scheme
Certificate Number ENP 407

Scissors



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications