



Interface® | UR102


SPECIFICATION


Product definition	Tapestry Tufted Patterned Structured Loop Tile	Style number	32710
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post- consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	859g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Total Weight	4838g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	2.4 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	7.3 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551/EN 986)
Gauge/Ends per 10cm	1/10 - 39.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Tufts per m²	110,320 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.2%)


CE
06
0336-CPD-8538



Cfl-s1



DB



EN 1307



≤10⁹Ω



Non-Directional



Quarter Turn



GUT



Pending



24 dB











33











Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com