




Interface® | UR301


SPECIFICATION


Product definition	Tapestry Tufted Patterned Structured Tip Sheared Tile	Style number	32713
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post- consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	842g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Total Weight	4821g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	2.4 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	7.5 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551/EN 986)
Gauge/Ends per 10cm	1/10 - 39.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Tufts per m²	122,140 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.2%)



 06
 0336-CPD-8538



Cfl-s1



DB



Non-Directional


GUT


Pending


24 dB


≤10⁹Ω


Hand

EN 1307

www.interface.com



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.