




Interface® | Vermont


SPECIFICATION


Product definition	Tufted Cut and Loop Tile	Style number	3381000405
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	747g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501)
Total Weight	4774g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	3.9 ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	7.2 ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	5/64 - 50.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	216,720 ± 5%	Colour Fastness - Light	6 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.15%)



 06
 0336-CPD-8538



 Bfl-s1



 BS



 EN 1307



 Ashlar



 Brick



 Quarter Turn



 Non-Directional



 GUT



 24742



 27dB


 33


 EMS 32802


 BSI


 UL A1


 FM 00679



Mission Zero:
 our promise to eliminate
 any negative impact our company
 may have on the environment
 by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications