


# Interface®

## Biosfera I Micro


<b>Product definition</b>	Microtuff Patterned Level Loop Tile					
<b>Pile Material</b>	100% Recycled Solution Dyed Nylon					
<b>Pile Yarn Weight</b>	350g/m <sup>2</sup> ± 5%					
<b>Total Weight</b>	4134g/m <sup>2</sup> ± 5%					
<b>Pile Height</b>						
<b>Total Thickness</b>	4.8 mm ± 0,5 mm					
<b>Gauge/Ends per 10cm</b>	5/64 - 50,4					
<b>Tufts per m2</b>	186,480 ± 5%					
<b>Backing Type</b>	Graphlex®					
<b>Wear Classification</b>	EN 1307 33 Heavy Contract					
<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass CfI S1 (EN ISO 13501)					
<b>Dimensional Stability</b>	≤ 0,2% (ISO 2551 / EN 986)					
<b>Impact Sound Insulation (ΔLw)</b>	13 dB (EN ISO 10140-3)					
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0.15 (EN ISO 11654)					
<b>Sound Absorption</b>						
<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0.01	0.02	0.03	0.13	0.21	0.24	α <sub>s</sub>
<b>Style number</b>	60717	5 - 20 Tiles per Box (50 x 50 cm ± 0,20%)				













**EN 14041**






DOP: 1037/118969  
textile floor covering  
EN 1307

QUARTER-TURN



 33  
 W  
 CfI-S1  
 OS  
  
 13 dB  
 0.15  
 ≥ 7  
  
  
 ≥ 2,4  




 Cert. ENP 477

install with TacTiles®

Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any negative impact our company may have on the environment by the year 2020.