


# Interface®














## Microsfera

<b>Product definition</b>	Microtuft Plain Level Loop Tile					
<b>Pile Material</b>	100% Polypropylene					
<b>Pile Yarn Weight</b>	474gr/m <sup>2</sup> ± 5%					
<b>Total Weight</b>	3764gr/m <sup>2</sup> ± 5%					
<b>Pile Height</b>						
<b>Total Thickness</b>	3,6mm ± 0,5mm					
<b>Gauge/Ends per 10cm</b>	5/64 - 50,4					
<b>Tufts per m2</b>	171,360 ± 5%					
<b>Backing Type</b>	Graphlex®					
<b>Wear Classification</b>	EN 1307 33 Heavy Contract					
<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)					
<b>Dimensional Stability</b>	≤ 0,2% (ISO 2551/ EN 986)					
<b>Impact Sound Insulation (ΔLw)</b>	12 dB (EN ISO 10140-3)					
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0,15 (EN ISO 11654)					
<b>Sound Absorption</b>						
<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0,02	0,01	0,02	0,14	0,20	0,25	α <sub>s</sub>
<b>Style number</b>	4173					6m <sup>2</sup> - 24 Tiles per Box (25cm x 100cm ± 0,2%)

**EN 14041**



DOP: 1037/122305  
textile floor covering  
**EN 1307**


 33
  W
  Cfl-s1
  05
 
 12 dB
  0,15
  ≥ 7
 

 ≥ 2,4
 

**D9F1C2D7**  
www.pro-tilt.info

www.pro-tilt.info

install with TacTiles®

Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any negative impact our company may have on the environment by the year 2020.