


Interface®

Touch & Tones 103

| | | | | | | |
|--------------------------------------|---|--------------|---------------|---------------|---------------|---|
| Product definition | Tufted Plain Shag Cut Tile | | | | | |
| Pile Material | 100% Nylon | | | | | |
| Pile Yarn Weight | 1314 g/m ² ± 5% | | | | | |
| Total Weight | 4764 g/m ² ± 5% | | | | | |
| Pile Height | 7.2 ± 0.5 mm | | | | | |
| Total Thickness | 10.6 ± 0.5 mm | | | | | |
| Gauge/Ends per 10cm | 5/16 - 12.6 | | | | | |
| Tufts per m2 | 42840 ± 5% | | | | | |
| Backing Type | Graphlex® | | | | | |
| Wear Classification | EN 1307 33 Heavy Contract | | | | | |
| Radiant panel | (EN ISO 9239/1) Euroclass CfI S1 (EN ISO 13501) | | | | | |
| Dimensional Stability | ≤ 0,2% (ISO 2551 / EN 986) | | | | | |
| Impact Sound Insulation (ΔLw) | 25 dB (EN ISO 10140-3) | | | | | |
| Rating of Sound Absorption | α _w 0.20 (EN ISO 11654) | | | | | |
| Sound Absorption | | | | | | |
| 125Hz | 250Hz | 500Hz | 1000Hz | 2000Hz | 4000Hz | (EN ISO 354) |
| 0.02 | 0.07 | 0.12 | 0.27 | 0.41 | 0.56 | α _s |
| Style number | 4176 | | | | | 3 m ² - 12 Tiles per Box (50 cm x 50 cm ± 0.20%) |











EN 14041




DOP: 1037/121927
textile floor covering
EN 1307

BFC53AA4
www.pro-enl.info

install with TacTiles®



Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any negative impact our company may have on the environment by the year 2020.